

Certificate of Compliance

Certificate: 1487022 Master Contract: 163694

Project: 2356373 **Date Issued:** October 26, 2010

Issued to: Exlar Corporation

1470 Lake Dr W

Chanhassen, MN 55317

USA

Attention: Gene Larson

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.



Rawn Murphy

Issued by: Rawn Murphy

PRODUCTS

CLASS 3228 02 - VALVES - Actuators - For Hazardous Locations

CLASS 3228 82 - VALVES - Actuators - For Hazardous Locations-Certified to U.S. Standard

Class I Division 1 Groups B, C, D

ER115 Series Rotary Actuators, Rated: 24 / 48 VDC or 115 to 460 VAC, 27 Amp maximum OR 33 Amp maximum, 50/60 Hertz. Temperature Code T3B (for models with 33 Amp maximum rating) OR T4 (for models with 27 Amp maximum rating); Ambient Temperature Rating is +80°C.

Notes:

This report covers certification of the actuator only. The associated electronic controller(s) required for the use of the actuator are not covered in this report. The suitability of the controller-actuator combination is based upon acceptance of the authority having jurisdiction.

Alpha-numeric suffixes may appear after the model number for descriptive purposes only.

DQD 507 Rev. 2009-09-01 Page: 1



Certificate: 1487022 Master Contract: 163694

Project: 2356373 **Date Issued:** October 26, 2010

APPLICABLE REQUIREMENTS

CAN/CSA Standard C22.2 No. 0-M91(Reaffirmed	General Requirements - Canadian Electrical Code, Part
2006)	II
CAN/CSA Standard C22.2 No. 0.4-04 (Reaffirmed	Bonding of electrical equipment
2009)	
CSA Standard C22.2 No. 0.5-1982 (Reaffirmed 2003)	
CAN/CSA Standard C22.2 No. 30-M1986 (Reaffirmed	Explosion-Proof Enclosures for Use in Class I
/	Hazardous Locations Industrial Products
CAN/CSA Standard C22.2 No. 139-1982 (Reaffirmed	Electrically Operated Valves
2005)	
UL Standard 429 (Fourth Edition)	Electrically Operated Valves
UL Standard 1002 (Seventh Edition)	Electrically Operated Valves for Use in Hazardous
	(Classified) Locations

DQD 507 Rev. 2009-09-01 Page: 2